




EZ1 100Plus

The "All-Purpose" desktop thermal transfer printer for light to medium duty applications

GoDEX EZ1 100Plus is a Value-priced reliable desktop printer which is perfect for medium duty applications. With its highly stability and durability, EZ1 100Plus is still the best choice for most general applications.



Large 300M ribbon capacity and 5" media roll



Free USB cable and sample media included with every printer



Options include: rotary cutter, label dispenser, CF card adapter with RTC, and Ethernet card



Free GoLabel label design software for ease of use and maximizing barcode printing efficiency

EZ1100 Plus

Desktop Printer

Barcodes Made Easy

Model		EZ1100 Plus
Print Method		Thermal Transfer / Direct Thermal
Resolution		203 dpi (8 dot/mm)
Print Speed		4 IPS (102 mm/s)
Print Width		4.25" (108 mm)
Print Length		Min. 0.16" (4 mm)** ; Max. 68" (1727 mm)
Memory	Flash	4MB Flash (2MB for user storage)
	SDRAM	8MB SDRAM
Sensor Type		Adjustable reflective sensor Fixed transmissive sensors, central aligned
Media	Types	Continuous form, gap labels, black mark sensing and punched hole; label length set by auto sensing or programming.
	Width	1" (25.4 mm) Min. – 4.64" (118 mm) Max.
	Thickness	0.003" (0.06 mm) Min. - 0.01" (0.25 mm) Max.
	Label Roll Diameter	Max. 5" (127 mm)
Ribbon	Core Diameter	1", 1.5", 3" (25.4 mm, 38.1 mm, 76.2 mm)
	Types	Wax, wax/resin, resin
	Length	981' (300 m)
	Width	1.18" Min. – 4.33" (30 mm - 110 mm) Max.
Ribbon Roll Diameter	Ribbon Roll Diameter	2.67" (68 mm)
	Core Diameter	1" (25.4 mm)
Printer Language		EZPL, GEPL (Godex Eltron® Printer Language), GZPL (Godex Zebra® Printer Language)
Software	Label Design Software	QLabel-IV (for EZPL only)
	Driver	Windows 2000 / XP / VISTA / Windows 7 / Windows 8.1
	DLL	Win CE , .NET , Windows Mobile, Windows 2000 / XP / VISTA / Windows 7 / Windows 8.1 / Android
Resident Fonts	Bitmap Fonts	6, 8, 10, 12, 14, 18, 24, 30, 16X26 and OCR A & B Bitmap fonts 90°, 180°, 270° rotatable, single characters 90°, 180°, 270° rotatable Bitmap fonts 8 times expandable in horizontal and vertical directions
	TTF Fonts	TTF fonts (Bold / Italic / Underline). 0°, 90°, 180°, 270° rotatable
Download Fonts	Bitmap Fonts	90°, 180°, 270° rotatable, single characters 90°, 180°, 270° rotatable
	Asian Fonts	16x16, 24x24. Traditional Chinese (BIG-5), Simplified Chinese(GB2312), Japanese (S-JIS), Korean (KS-X1001) 90°, 180°, 270° rotatable and 8 times expandable in horizontal and vertical directions
	TTF Fonts	90°, 180°, 270° rotatable
Barcodes	1-D Bar Codes	Code 39, Code 93, Code 128 (subset A, B, C), UCC/EAN-128 K-Mart, UCC/EAN-128, UPC A / E (add on 2 & 5), 1 2 of 5, 1 2 of 5 with Shipping Bearer Bars, EAN 8 / 13 (add on 2 & 5), Codabar, Post NET, EAN 128, DUN 14, HIBC, MSI (1 Mod 10), Random Weight, Telepen, FIM, China Postal Code, RPS 128 and GS1 DataBar
	2-D Bar Codes	PDF417, Datamatrix code, MaxiCode, QR code and Micro QR code
Code Pages		Codepage 437, 850, 851, 852, 855, 857, 860, 861, 862, 863, 865, 866, 869, 737 Windows 1250, 1251, 1252, 1253, 1254, 1255 Unicode UTF8, UTF16BE , UTF16LE
Graphics		Resident graphic file types are BMP and PCX, other graphic formats are downloadable from the software
Interfaces		Serial port: RS-232 (DB-9) USB port (default on) Parallel port: Centronics 36-pin
Control Panel		Two bi-color status-LEDs: Ready & Status Control key: FEED
Power		Auto Switching 100-240VAC, 50-60Hz
Environment	Operation Temperature	41°F to 104°F (5°C to 40°C)
	Storage Temperature	-4°F to 122°F (-20°C to 50°C)
Humidity	Operation	30-85%, non-condensing
	Storage	10-90%, non-condensing
Agency Approvals		CE(EMC), FCC Class A, CB, cUL, CCC
Dimension	Length	11.2" (285 mm)
	Height	6.8" (171 mm)
	Width	8.9" (226 mm)
Weight		6 lbs (2.72 Kg), excluding consumables
Options & Accessories		Rotary Cutter Label Dispenser External label roll holder for 10" (250 mm) O.D. label rolls External label rewinder CF card adapter with real time clock (max. 1GB CF card) Ethernet 10/100Mbps print server (default off; disable USB when in use) 802.11 b/g wireless print server (Default off; disables USB when in use. Must remove PS2 port and Ethernet card to install)

* Specifications are subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective owners.

** Minimum print height and maximum print speed specification compliance can be dependent on non-standard material variables such as label type, thickness, spacing, liner construction, etc. Godex is pleased to test non-standard materials for minimum print height and maximum print speed capability. Godex is pleased to test non-standard materials for minimum height printing capability.